

HRI-Mei

The data interface and flexible pulse output for Bulk Water Meters



Description

The HRI-Mei is a data capture device for MeiStream and MeiTwin MID bulk water meters. All MeiStream standard registers are prepared to receive the HRI-Mei.

The HRI-Mei can also be mounted afterwards without breaking the meter's seal.

The HRI-Mei provides a high resolution pulse output with water flow direction detection.

Also the data interface can be used for M-Bus applications or for MiniBus devices like MiniPad or Sensus((S))cout-MB

With the HRI-Mei all known data interfaces with Encoder, Electronic and Hybrid registers can be replaced.

Depending on the register a second pulser like the Opto OD can be plugged in additionally e.g. at the MeiStream.

Also other applications requiring reed switches or optical pulse outputs can be supported with only this one data capture device.

Special Features

Compatible to bulk water meters with MeiStream and MeiTwin MID standard register

Load-free inductive scanning of the meter's pointer

Retrofittable

Detection of water flow direction

Electronic pulse output means no switch bouncing

Pulse-weight, mode and length can be changed on site

Self diagnostic and tamper detection


Battery lifetime up to 12 years. With external power supply i.e. a M-Bus central unit lifetime can be expanded

Sealed housing (IP68)

Cable length 3 m

Technical Data

cable length 3 m



Pulse output

According to pulse mode
Opto-OD (NAMUR) compatible:
programmable pulse weights
(10, 25, ..., 1000) litre/pulse
Pulse length 6ms
NAMUR acc. EN 60947-5-6
Reed-RD compatible:
programmable pulse weights
(10, 25, ..., 10000) litre/pulse
Pulse length 32, 128 or 500ms
max. Voltage 48 Vdc
max. current 0,2 A
max. switching capacity 4 W

Data interface

M-Bus and MiniBus (autodetected)

Autom. detection of baud rate (300/2400Bd) and type of interface.

Data protocol according IEC870-5/EN1434-3

An Encoder mode provides an easy to use data protocol compatible to the encoder registers.

Transferred Data

Meter index

Fabrication number

Meter ID. equivalent to secondary address

Monthly meter index for programmable day

Meter index for programmable yearly key date and for the year before

Min./max. water flow with date/time

Backward water volume with date/time

Broken pipe and leakage detection with programmable flow thresholds

Tamper detection (*)

The HRI-Mei can be programmed to transfer selected information.

Programmable Data

All changeable data can be set with MiniCom software via the M-Bus / MiniBus data interface. MiniCom download is free of charge from the Sensus web site.

(*) Requires tamper target at the meter.

Pulse Modes

The HRI-Mei provides 7 different pulse output modes via 2 lines.

Parallel usage of the pulse output and serial output is not recommended and may cause problems depending on the application.

Mode B1:

is used for remote pulse collectors with only one pulse input.

I1: balanced pulses (*)

I2: alarm (**)

(*) Backward pulses are compensated by suppressing the same quantity of forward pulses

(**) alarms can be programmed for broken pipe, leakage, tampering, cable cut and indicated by ground level at the output.

Mode B2:

I1: Forward pulses

I2: Backward pulses

Mode B3:

I1: For-/Backward pulses

I2: signal for the flow direction (*)

(*) Ground level means reverse flow

Mode B4 (default):

as mode B1, but line I2 is inverted

Mode B5:

Opto-OD (NAMUR) pulse output (6 ms)

I1: pulses with flow direction code

I2: not used

Mode B6:

NAMUR (as OD-AM) pulse output (7 ms)

I1: balanced pulses as mode B1

I2: not used

Mode B7:

Dual pulse output

I1: balanced pulses as mode B1

I2: same as I1

Temperature range:

HRI-Mei standard for cold water (30 °C) and warm water (50 °C).

Environmental temperature range: -10 °C ... +60 °C

Possible pulse values

Pulse value		10			50			100			250			500		
Pulse length		32	128	500	32	128	500	32	128	500	32	128	500	32	128	500
10 l pointer	40 DN	x	x	-	x	x	x	x	x	x	x	x	x	x	x	x
	50 DN	x	x	-	x	x	x	x	x	x	x	x	x	x	x	x
	65 DN	x	x	-	x	x	x	x	x	x	x	x	x	x	x	x
	80 DN	x	-	-	x	x	x	x	x	x	x	x	x	x	x	x
	100 DN	x	-	-	x	x	-	x	x	x	x	x	x	x	x	x
	125 DN	x		-	x	x	-	x	x	x	x	x	x	x	x	x
100 l pointer	150 DN	not possible						x	x	-	x	x	x	x	x	x
	200 DN	not possible						x	x	-	x	x	x	x	x	x
	250 DN	not possible						x	x	-	x	x	-	x	x	x
	300 DN	not possible						x	-	-	x	x	-	x	x	x

Classical Sensus pulsers and equivalent HRI-Mei mode

Previous pulse outputs	Litres/pulse
RD01, RD011	10 to 100.000 lpp
OD01, OD03, OD07-L, OD07-24V, OD07-24S	10 to 1.000 lpp
OD AM	10 to 1.000 lpp
OD02/EX(cold), special HRI-Mei variant	10 to 1.000 lpp

10 litre per pulses with 32 ms pulse length only.
 All other pulse weights can be set to 500 ms pulse length.
 For DN150-300 min pulse weight 100 lpp.

Order Information

HRI-Mei variant (examples *)	Settings	Application	Order no.
HRI-Mei/B1/D10/T500/50 °C	Pulse Mode 1 (open collector) Pulse weight 100 lpp Pulse length 500ms	Cold water for DN40....125	MEI1ACG2XX
HRI-Mei/B1D1/T32/50 °C	Pulse Mode 1 (open collector) Pulse weight 10 lpp Pulse length 32ms	Cold water for DN40....125	MEI1AAD2XX
HRI-Mei/B5/D1/T6/50 °C	Pulse Mode 5 (Namur) Pulse weight 10 lpp Pulse length 6ms	Cold water for DN40....125	MEI1EDD2XX
HRI-Mei-CDL/D1/50 °C	Pulse Mode 2 Pulse weight 10 lpp With CDL plug	CDL data logging Cold water for DN40....125	MEI3XXD2XX
HRI-Mei/B1/D10/T500/50 °C	Pulse Mode 1 (open collector) Pulse weight 1000 lpp Pulse length 500ms	Cold water for DN 150.....300	MEI1ACK3XX
HRI-Mei/B1D1/T32/50 °C	Pulse Mode 1 (open collector), Pulse weight 100 lpp, Pulse length 32ms	Cold water for DN 150...300	MEI1AAG3XX
HRI-Mei/B5/D1/T6/50 °C	Pulse Mode 5 (Namur) Pulse weight 100 lpp Pulse length 6ms	Cold water for DN 150.....300	MEI1EDG3XX
HRI-Mei-CDL/D1/50 °C	Pulse Mode 2 Pulse weight 100 lpp With CDL plug	CDL data logging Cold water for DN 150.....300	MEI3XXG3XX

**Further variants on request.